

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (currently amended): A communication system comprising:
 - (a) an amplifier which receives a communication signal, the amplifier being controlled by an ~~amplitude~~ amplification control signal; and
 - (b) an insertion phase variation compensation module which counteracts the effects of a phase offset intermittently introduced into the communication signal when the amplifier is either enabled or disabled in response to the amplification control signal, wherein the communication signal is amplified by the amplifier when the amplifier is enabled, and the communication signal is not amplified by the amplifier when the amplifier is ~~disabled~~ disabled;
 - (c) a processor which generates the amplification control signal; and
 - (d) a look up table (LUT) in communication with the processor and the insertion phase variation compensation module, wherein the LUT receives the amplification control signal from the processor and provides an estimate of the phase offset to the insertion phase variation compensation module as a function of the amplification control signal, the provided estimate includes a Sin function and a Cos function of the phase offset, x, the insertion phase variation compensation module has a real, Re, input associated with a digital in-phase (I) signal component and an imaginary, Im, input associated with a quadrature (Q) signal component and, based on the estimate provided by the LUT, the insertion phase variation compensation module outputs an I signal component having a phase that is adjusted in accordance with the following function: $(\text{Cos}(x) \times \text{Re}) - (\text{Sin}(x) \times \text{Im})$.

2. (currently amended): The communication system of claim 1 further comprising:

(e) ~~(e)~~ a receiver which receives the communication signal from the amplifier and outputs analog in-phase (I) and quadrature (Q) signal components; and

(f) ~~(d)~~ an analog to digital converter (ADC) which receives the analog I and Q signal components from the receiver and converts the analog [✓] signal components to digital I and Q signal components. *I and Q*

3. (currently amended): The communication system of claim 2 wherein the insertion phase variation compensation module receives the digital I and Q signal components from the ADC and outputs altered I and Q signal components having different phase characteristics than the digital I and Q components, the communication system further comprising:

(g) ~~(e)~~ a modem which receives the altered I and Q signal components, the modem including a processor which generates the amplification control signal.

4. (original): The communication system of claim 3 wherein the processor calculates how much power is input to the ADC.

5. (original): The communication system of claim 2 wherein the insertion phase variation compensation module receives the digital I and Q components from the ADC and alters the phase characteristics of the digital I and Q components as a function of the amplification control signal.

Claims 6-8 (canceled)

¹² 9. (currently amended): A communication system comprising:

(a) an amplifier which receives a communication signal, the amplifier being controlled by an amplification control signal;

(b) an insertion phase variation compensation module which counteracts the effects of a phase offset intermittently introduced into the communication signal when the amplifier is either enabled or disabled in response to the amplification control signal, wherein the communication signal is amplified by the amplifier when the amplifier is enabled, and the communication signal is not amplified by the amplifier when the amplifier is disabled;

(c) a processor which generates the amplification control signal; and

(d) a look up table (LUT) in communication with the processor and the insertion phase variation compensation module, wherein the LUT receives the amplification control signal from the processor and provides an estimate of the phase offset to the insertion phase variation compensation module as a function of the amplification control signal, wherein the provided estimate includes a Sin function and a Cos function of the phase offset, x, The communication system of claim 7 wherein the insertion phase variation compensation module has a real input, Re, associated with a digital in-phase (I) signal component and an imaginary input, Im, associated with a quadrature (Q) signal component and, based on the estimate provided by the LUT, the insertion phase variation compensation module outputs a Q signal component having a phase that is adjusted in accordance with the following function: $(\text{Sin}(x) \times \text{Re}) + (\text{Cos}(x) \times \text{Im})$.

⁶ 10. (original): The communication system of claim 1 wherein the communication signal includes first and second time slots separated by a guard

period, and the amplification control signal is provided to the amplifier during the guard period after data in the first time slot is received by the amplifier and is processed.

7 ~~11~~. (original): The communication system of claim 1 wherein the communication signal includes first and second time slots separated by a guard period, and the amplifier is either enabled or disabled during the guard period after data in the first time slot is received by the amplifier and is processed.

8 ~~12~~. (currently amended): The communication system of claim ~~11~~⁷ wherein when data in the first time slot is received by the amplifier when ~~it is~~ the amplifier is disabled, the data in the second time slot is received by the amplifier when ~~it is~~ the amplifier enabled.

9 ~~13~~. (currently amended): The communication system of claim ~~11~~⁷ wherein when data in the first time slot is received by the amplifier when ~~it is~~ the amplifier is enabled, the data in the second time slot is received by the amplifier when ~~it is~~ the amplifier disabled.

10 ~~14~~. (currently amended): The communication system of ~~claim 6~~ claim 1 wherein the communication signal includes first and second time slots separated by a guard period, and the estimate of the phase offset is provided to the insertion phase variation compensation module during the guard period after data in the first time slot is received by the amplifier and is processed.

11 15. (currently amended): The communication system of ~~claim 6~~ claim 1 wherein the communication signal includes first and second time slots separated by a guard period, and the insertion phase variation compensation module adjusts the phase of the communication signal based on the provided estimate during the guard period after data in the first time slot is received by the amplifier and is processed.

23 16. (currently amended): A wireless transmit/receive unit (WTRU) comprising:

(a) an amplifier which receives a communication signal, the amplifier being controlled by an ~~amplitude~~ amplification control signal; and

(b) an insertion phase variation compensation module which counteracts the effects of a phase offset intermittently introduced into the communication signal when the amplifier is either enabled or disabled in response to the amplification control signal, wherein the communication signal is amplified by the amplifier when the amplifier is enabled, and the communication signal is not amplified by the amplifier when the amplifier is ~~disabled~~ disabled;

(c) a processor which generates the amplification control signal; and

(d) a look up table (LUT) in communication with the processor and the insertion phase variation compensation module, wherein the LUT receives the amplification control signal from the processor and provides an estimate of the phase offset to the insertion phase variation compensation module as a function of the amplification control signal, the provided estimate includes a Sin function and a Cos function of the phase offset, x, the insertion phase variation compensation module has a real, Re, input associated with a digital in-phase (I) signal component and an imaginary, Im, input associated with a quadrature (Q) signal component and, based on the estimate provided by the LUT, the insertion phase variation

compensation module outputs an I signal component having a phase that is adjusted in accordance with the following function: $(\cos(x) \times \text{Re}) - (\sin(x) \times \text{Im})$.

²³
24 17. (currently amended): The WTRU of claim 16 further comprising:

(e) (e) a receiver which receives the communication signal from the amplifier and outputs analog in-phase (I) and quadrature (Q) signal components; and

(f) (d) an analog to digital converter (ADC) which receives the analog I and Q signal components from the receiver and converts the analog signal components to digital I and Q signal components. ^{I and Q}

²⁴
25 18. (currently amended): The WTRU of claim 17 wherein the insertion phase variation compensation module receives the digital I and Q signal components from the ADC and outputs altered I and Q signal components having different phase characteristics than the digital I and Q components, the WTRU further comprising:

(g) (e) a modem which receives the altered I and Q signal components, the modem including a processor which generates the amplification control signal.

²⁵
26 19. (original): The WTRU of claim 18 wherein the processor calculates how much power is input to the ADC.

²⁴
27 20. (original): The WTRU of claim 17 wherein the insertion phase variation compensation module receives the digital I and Q components from the ADC and alters the phase characteristics of the digital I and Q components as a function of the amplification control signal.

Claims 21-23 (canceled)

34 24. (currently amended): A wireless transmit/receive unit (WTRU) comprising:

(a) an amplifier which receives a communication signal, the amplifier being controlled by an amplification control signal;

(b) an insertion phase variation compensation module which counteracts the effects of a phase offset intermittently introduced into the communication signal when the amplifier is either enabled or disabled in response to the amplification control signal, wherein the communication signal is amplified by the amplifier when the amplifier is enabled, and the communication signal is not amplified by the amplifier when the amplifier is disabled;

(c) a processor which generates the amplification control signal; and

(d) a look up table (LUT) in communication with the processor and the insertion phase variation compensation module, wherein the LUT receives the amplification control signal from the processor and provides an estimate of the phase offset to the insertion phase variation compensation module as a function of the amplification control signal, the provided estimate includes a Sin function and a Cos function of the phase offset, x. The WTRU of claim 22 wherein the insertion phase variation compensation module has a real input, Re, associated with a digital in-phase (I) signal component and an imaginary input, Im, associated with a quadrature (Q) signal component and, based on the estimate provided by the LUT, the insertion phase variation compensation module outputs a Q signal component having a phase that is adjusted in accordance with the following function: $(\sin(x) \times \text{Re}) + (\cos(x) \times \text{Im})$.

28 25. (original): The WTRU of claim ²³16 wherein the communication signal includes first and second time slots separated by a guard period, and the amplification control signal is provided to the amplifier during the guard period after data in the first time slot is received by the amplifier and is processed.

30 26. (currently amended): The WTRU of ~~claim 25~~ ²⁹claim 28 wherein when data in the first time slot is received by the amplifier when it is the amplifier is disabled, the data in the second time slot is received by the amplifier when it is *the amplifier* enabled.

31 27. (currently amended): The WTRU of ~~claim 25~~ ²⁹claim 28 wherein when data in the first time slot is received by the amplifier when it is the amplifier is enabled, the data in the second time slot is received by the amplifier when it is *the amplifier* disabled.

29 28. (original): The WTRU of claim ²³16 wherein the communication signal includes first and second time slots separated by a guard period, and the amplifier is either enabled or disabled during the guard period after data in the first time slot is received by the amplifier and is processed.

32 29. (currently amended): The WTRU of ~~claim 21~~ ²³claim 16 wherein the communication signal includes first and second time slots separated by a guard period, and the estimate of the phase offset is provided to the insertion phase variation compensation module during the guard period after data in the first time slot is received by the amplifier and is processed.

33 30. (currently amended): The WTRU of ~~claim 21~~ ²³ claim 16 wherein the communication signal includes first and second time slots separated by a guard period, and the insertion phase variation compensation module adjusts the phase of the communication signal based on the provided estimate during the guard period after data in the first time slot is received by the amplifier and is processed.

45 31. (currently amended): An integrated circuit (IC) comprising:

(a) an amplifier which receives a communication signal, the amplifier being controlled by an amplitude amplification control signal; and

(b) an insertion phase variation compensation module which counteracts the effects of a phase offset intermittently introduced into the communication signal when the amplifier is either enabled or disabled in response to the amplification control signal, wherein the communication signal is amplified by the amplifier when the amplifier is enabled, and the communication signal is not amplified by the amplifier when the amplifier is ~~disabled~~ disabled;

(c) a processor which generates the amplification control signal; and

(d) a look up table (LUT) in communication with the processor and the insertion phase variation compensation module, wherein the LUT receives the amplification control signal from the processor and provides an estimate of the phase offset to the insertion phase variation compensation module as a function of the amplification control signal, the provided estimate includes a Sin function and a Cos function of the phase offset, x, the insertion phase variation compensation module has a real, Re, input associated with a digital in-phase (I) signal component and an imaginary, Im, input associated with a quadrature (Q) signal component and, based on the estimate provided by the LUT, the insertion phase variation

compensation module outputs an I signal component having a phase that is adjusted in accordance with the following function: $(\cos(x) \times \text{Re}) - (\sin(x) \times \text{Im})$.

46 32. (currently amended): The IC of claim ⁴⁵31 further comprising:

(e) ~~(e)~~ a receiver which receives the communication signal from the amplifier and outputs analog in-phase (I) and quadrature (Q) signal components; and

(f) ~~(d)~~ an analog to digital converter (ADC) which receives the analog I and Q signal components from the receiver and converts the analog ⁴⁶signal components to digital I and Q signal components. I and Q

47 33. (currently amended): The IC of claim ⁴⁶32 wherein the insertion phase variation compensation module receives the digital I and Q signal components from the ADC and outputs altered I and Q signal components having different phase characteristics than the digital I and Q components, the IC further comprising:

(g) ~~(e)~~ a modem which receives the altered I and Q signal components, the modem including a processor which generates the amplification control signal.

48 34. (original): The IC of claim ⁴⁷33 wherein the processor calculates how much power is input to the ADC.

49 35. (original): The IC of claim ⁴⁶32 wherein the insertion phase variation compensation module receives the digital I and Q components from the ADC and alters the phase characteristics of the digital I and Q components as a function of the amplification control signal.

Claims 36-38 (canceled)

56 39. (currently amended): An integrated circuit (IC) comprising:

(a) an amplifier which receives a communication signal, the amplifier being controlled by an amplification control signal;

(b) an insertion phase variation compensation module which counteracts the effects of a phase offset intermittently introduced into the communication signal when the amplifier is either enabled or disabled in response to the amplification control signal, wherein the communication signal is amplified by the amplifier when the amplifier is enabled, and the communication signal is not amplified by the amplifier when the amplifier is disabled;

(c) a processor which generates the amplification control signal; and

(d) a look up table (LUT) in communication with the processor and the insertion phase variation compensation module, wherein the LUT receives the amplification control signal from the processor and provides an estimate of the phase offset to the insertion phase variation compensation module as a function of the amplification control signal. The IC of claim 37 wherein the insertion phase variation compensation module has a real input, Re, associated with a digital in-phase (I) signal component and an imaginary input, Im, associated with a quadrature (Q) signal component and, based on the estimate provided by the LUT, the insertion phase variation compensation module outputs a Q signal component having a phase that is adjusted in accordance with the following function: $(\sin(x) \times \text{Re}) + (\cos(x) \times \text{Im})$.

50 40. (original): The IC of claim ⁴⁵31 wherein the communication signal includes first and second time slots separated by a guard period, and the

amplification control signal is provided to the amplifier during the guard period after data in the first time slot is received by the amplifier and is processed.

52 41. (currently amended): The IC of ~~claim 40~~ ⁵¹ claim 48 wherein when data in the first time slot is received by the amplifier when it is the amplifier is disabled, the data in the second time slot is received by the amplifier when it is enabled.
the amplifier

53 42. (currently amended): The IC of ~~claim 40~~ ⁵¹ claim 48 wherein when data in the first time slot is received by the amplifier when it is the amplifier is enabled, the data in the second time slot is received by the amplifier when it is disabled.
the amplifier

51 43. (original): The IC of ~~claim 37~~ ⁴⁵ claim 31 wherein the communication signal includes first and second time slots separated by a guard period, and the amplifier is either enabled or disabled during the guard period after data in the first time slot is received by the amplifier and is processed.

54 44. (currently amended): The IC of ~~claim 36~~ ⁴⁵ claim 31 wherein the communication signal includes first and second time slots separated by a guard period, and the estimate of the phase offset is provided to the insertion phase variation compensation module during the guard period after data in the first time slot is received by the amplifier and is processed.

55 45. (currently amended): The IC of ~~claim 36~~ ⁴⁵ claim 31 wherein the communication signal includes first and second time slots separated by a guard period, and the insertion phase variation compensation module adjusts the phase of

the communication signal based on the provided estimate during the guard period after data in the first time slot is received by the amplifier and is processed.

67 46. (currently amended): In a communication system including an amplifier and an insertion phase variation compensation module, a method of counteracting the effects of a phase offset intermittently introduced into a communication signal when the amplifier is enabled, the method comprising:

(a) providing an amplification control signal to the amplifier when ~~it is~~ the amplifier is disabled;

(b) enabling the amplifier in response to the amplification control signal, the enabling of the amplifier causing a phase offset to be introduced into the communication signal;

(c) providing an estimate of the phase offset to the insertion phase variation compensation module as a function of the amplification control signal; and

(d) the insertion phase variation compensation module adjusting the phase of the communication signal based on the provided estimate, wherein the provided estimate includes a Sin function and a Cos function of the phase offset, x, the insertion phase variation compensation module has a real, Re, input associated with a digital in-phase (I) signal component and an imaginary, Im, input associated with a quadrature (Q) signal component and, based on the ^{provided} estimate provided by the LUT, the insertion phase variation compensation module outputs an I signal component having a phase that is adjusted in accordance with the following function: $(\text{Cos}(x) \times \text{Re}) - (\text{Sin}(x) \times \text{Im})$.

Claims 47 and 48 (canceled)

73 49. (currently amended): In a communication system including an amplifier and an insertion phase variation compensation module, a method of counteracting the effects of a phase offset intermittently introduced into a communication signal when the amplifier is enabled, the method comprising:

(a) providing an amplification control signal to the amplifier when the amplifier is disabled;

(b) enabling the amplifier in response to the amplification control signal, the enabling of the amplifier causing a phase offset to be introduced into the communication signal;

(c) providing an estimate of the phase offset to the insertion phase variation compensation module as a function of the amplification control signal; and

(d) the insertion phase variation compensation module adjusting the phase of the communication signal based on the provided estimate, wherein the provided estimate includes a Sin function and a Cos function of the phase offset, x.
~~The method of claim 47 wherein~~ the insertion phase variation compensation module has a real input, Re, associated with a digital in-phase (I) signal component and an imaginary input, Im, associated with a quadrature (Q) signal component and, based on the ^{provided} estimate ~~provided by the LUT~~, the insertion phase variation compensation module outputs a Q signal component having a phase that is adjusted in accordance with the following function: $(\text{Sin}(x) \times \text{Re}) + (\text{Cos}(x) \times \text{Im})$.

68 50. (original): The method of claim ⁶⁷46 wherein the communication signal includes first and second time slots separated by a guard period, and at least one of steps (a) - (d) are implemented during the guard period after data in the first time slot is received by the amplifier and is processed.

69 51. (currently amended): The method of claim ⁶⁷46 wherein the communication signal includes first and second time slots separated by a guard period such that data in the first time slot is received by the amplifier when ~~it is~~ the amplifier is disabled and data in the second time slot is received by the amplifier when ~~it is~~ the amplifier is enabled.

70 52. (currently amended): In a communication system including an amplifier and an insertion phase variation compensation module, a method of counteracting the effects of a phase offset intermittently introduced into a communication signal when the amplifier is disabled, the method comprising:

(a) providing an amplification control signal to the amplifier when ~~it is~~ the amplifier is enabled;

(b) disabling the amplifier in response to the amplification control signal, the disabling of the amplifier causing a phase offset to be introduced into the communication signal;

(c) providing an estimate of the phase offset to the insertion phase variation compensation module as a function of the amplification control signal; and

(d) the insertion phase variation compensation module adjusting the phase of the communication signal based on the provided estimate, wherein the provided estimate includes a Sin function and a Cos function of a phase offset, x , the insertion phase variation compensation module has a real, Re , input associated with a digital in-phase (I) signal component and an imaginary, Im , input associated with a quadrature (Q) signal component and, based on the ^{provided} estimate ~~provided by the~~ provided by the ~~HUT~~, the insertion phase variation compensation module outputs an I signal component having a phase that is adjusted in accordance with the following function: $(\cos(x) \times Re) - (\sin(x) \times Im)$.

Claims 53 and 54 (canceled)

76 55. (currently amended): In a communication system including an amplifier and an insertion phase variation compensation module, a method of counteracting the effects of a phase offset intermittently introduced into a communication signal when the amplifier is disabled, the method comprising:

(a) providing an amplification control signal to the amplifier when the amplifier is enabled;

(b) disabling the amplifier in response to the amplification control signal, the disabling of the amplifier causing a phase offset to be introduced into the communication signal;

(c) providing an estimate of the phase offset to the insertion phase variation compensation module as a function of the amplification control signal; and

(d) the insertion phase variation compensation module adjusting the phase of the communication signal based on the provided estimate, wherein the provided estimate includes a Sin function and a Cos function of a phase offset, x . ~~The method of claim 53 wherein~~ the insertion phase variation compensation module has a real input, Re , associated with a digital in-phase (I) signal component and an imaginary input, Im , associated with a quadrature (Q) signal component and, based on the ^{provided} estimate ~~provided by the LUT~~, the insertion phase variation compensation module outputs a Q signal component having a phase that is adjusted in accordance with the following function: $(\sin(x) \times Re) + (\cos(x) \times Im)$.

77 56. (original): The method of claim ⁷⁰~~52~~ wherein the communication signal includes first and second time slots separated by a guard period, and at least

one of steps (a) - (d) are implemented during the guard period after data in the first time slot is received by the amplifier and is processed.

72 51. (currently amended): The method of claim ⁷⁰52 wherein the communication signal includes first and second time slots separated by a guard period such that data in the first time slot is received by the amplifier when ^{it is} ~~it is~~ ^{the amplifier} enabled and data in the second time slot is received by the amplifier when ~~it is~~ the amplifier is disabled.

13 58. (new): The communication system of claim ¹²9 further comprising:

(e) a receiver which receives the communication signal from the amplifier and outputs analog in-phase (I) and quadrature (Q) signal components; and

(f) an analog to digital converter (ADC) which receives the analog I and Q signal components from the receiver and converts the analog ^{I and Q} signal components to digital I and Q signal components.

14 59. (new): The communication system of claim ¹³58 wherein the insertion phase variation compensation module receives the digital I and Q signal components from the ADC and outputs altered I and Q signal components having different phase characteristics than the digital I and Q components, the communication system further comprising:

(g) a modem which receives the altered I and Q signal components, the modem including a processor which generates the amplification control signal.

15 60. (new): The communication system of claim ¹⁴59 wherein the processor calculates how much power is input to the ADC.

¹³
~~16~~ 61. (new): The communication system of claim ~~58~~ wherein the insertion phase variation compensation module receives the digital I and Q components from the ADC and alters the phase characteristics of the digital I and Q components as a function of the amplification control signal.

¹²
~~17~~ 62. (new): The communication system of claim ~~9~~ wherein the communication signal includes first and second time slots separated by a guard period, and the amplification control signal is provided to the amplifier during the guard period after data in the first time slot is received by the amplifier and is processed.

¹²
~~18~~ 63. (new): The communication system of claim ~~9~~ wherein the communication signal includes first and second time slots separated by a guard period, and the amplifier is either enabled or disabled during the guard period after data in the first time slot is received by the amplifier and is processed.

¹⁸
~~19~~ 64. (new): The communication system of claim ~~63~~ wherein when data in the first time slot is received by the amplifier when the amplifier is disabled, the data in the second time slot is received by the amplifier when ~~it is enabled~~.
the amplifier

¹⁸
~~20~~ 65. (new): The communication system of claim ~~63~~ wherein when data in the first time slot is received by the amplifier when the amplifier is enabled, the data in the second time slot is received by the amplifier when ~~it is disabled~~.
the amplifier

21 ~~66~~. (new): The communication system of claim ¹²8 wherein the communication signal includes first and second time slots separated by a guard period, and the estimate of the phase offset is provided to the insertion phase variation compensation module during the guard period after data in the first time slot is received by the amplifier and is processed.

22 ~~67~~. (new): The communication system of claim ¹²8 wherein the communication signal includes first and second time slots separated by a guard period, and the insertion phase variation compensation module adjusts the phase of the communication signal based on the provided estimate during the guard period after data in the first time slot is received by the amplifier and is processed.

35 ~~68~~. (new): The WTRU of claim ³⁴~~24~~ further comprising:

(e) a receiver which receives the communication signal from the amplifier and outputs analog in-phase (I) and quadrature (Q) signal components; and

(f) an analog to digital converter (ADC) which receives the analog I and Q signal components from the receiver and converts the analog ^{I and Q} signal components to digital I and Q signal components.

36 ~~69~~. (new): The WTRU of claim ³⁵~~68~~ wherein the insertion phase variation compensation module receives the digital I and Q signal components from the ADC and outputs altered I and Q signal components having different phase characteristics than the digital I and Q components, the WTRU further comprising:

(g) a modem which receives the altered I and Q signal components, the modem including a processor which generates the amplification control signal.

37 ³⁶70. (new): The WTRU of claim ~~69~~³⁶ wherein the processor calculates how much power is input to the ADC.

38 ³⁵71. (new): The WTRU of claim ~~68~~³⁵ wherein the insertion phase variation compensation module receives the digital I and Q components from the ADC and alters the phase characteristics of the digital I and Q components as a function of the amplification control signal.

39 ³⁴72. (new): The WTRU of claim ~~24~~³⁴ wherein the communication signal includes first and second time slots separated by a guard period, and the amplification control signal is provided to the amplifier during the guard period after data in the first time slot is received by the amplifier and is processed.

40 ³⁴73. (new): The WTRU of claim ~~24~~³⁴ wherein the communication signal includes first and second time slots separated by a guard period, and the amplifier is either enabled or disabled during the guard period after data in the first time slot is received by the amplifier and is processed.

41 ⁴⁰74. (new): The WTRU of claim ~~73~~⁴⁰ wherein when data in the first time slot is received by the amplifier when the amplifier is disabled, the data in the second time slot is received by the amplifier when ~~it~~^{the amplifier} is enabled.

42 ⁴⁰75. (new): The WTRU of claim ~~73~~⁴⁰ wherein when data in the first time slot is received by the amplifier when the amplifier is enabled, the data in the second time slot is received by the amplifier when ~~it~~^{the amplifier} is disabled.

43 76. (new): The WTRU of claim ³⁴24 wherein the communication signal includes first and second time slots separated by a guard period, and the estimate of the phase offset is provided to the insertion phase variation compensation module during the guard period after data in the first time slot is received by the amplifier and is processed.

44 77. (new): The WTRU of claim ³⁴24 wherein the communication signal includes first and second time slots separated by a guard period, and the insertion phase variation compensation module adjusts the phase of the communication signal based on the provided estimate during the guard period after data in the first time slot is received by the amplifier and is processed.

57 78. (new): The IC of claim ⁵⁶38 further comprising:

(e) a receiver which receives the communication signal from the amplifier and outputs analog in-phase (I) and quadrature (Q) signal components; and

(f) an analog to digital converter (ADC) which receives the analog I and Q signal components from the receiver and converts the analog ^{I and Q} signal components to digital I and Q signal components.

58 79. (new): The IC of claim ⁵⁷78 wherein the insertion phase variation compensation module receives the digital I and Q signal components from the ADC and outputs altered I and Q signal components having different phase characteristics than the digital I and Q components, the IC further comprising:

(g) a modem which receives the altered I and Q signal components, the modem including a processor which generates the amplification control signal.

⁵⁸
59 80. (new): The IC of claim 79 wherein the processor calculates how much power is input to the ADC.

⁵⁷
60 81. (new): The IC of claim 78 wherein the insertion phase variation compensation module receives the digital I and Q components from the ADC and alters the phase characteristics of the digital I and Q components as a function of the amplification control signal.

⁵⁶
61 82. (new): The IC of claim 39 wherein the communication signal includes first and second time slots separated by a guard period, and the amplification control signal is provided to the amplifier during the guard period after data in the first time slot is received by the amplifier and is processed.

⁵⁶
62 83. (new): The IC of claim 39 wherein the communication signal includes first and second time slots separated by a guard period, and the amplifier is either enabled or disabled during the guard period after data in the first time slot is received by the amplifier and is processed.

⁶²
63 84. (new): The IC of claim 83 wherein when data in the first time slot is received by the amplifier when the amplifier is disabled, the data in the second time slot is received by the amplifier when ^{the amplifier} it is enabled.

⁶²
64 85. (new): The IC of claim 83 wherein when data in the first time slot is received by the amplifier when the amplifier is enabled, the data in the second time slot is received by the amplifier when ^{the amplifier} it is disabled.

65 86. (new): The IC of claim ⁵⁶39 wherein the communication signal includes first and second time slots separated by a guard period, and the estimate of the phase offset is provided to the insertion phase variation compensation module during the guard period after data in the first time slot is received by the amplifier and is processed.

66 87. (new): The IC of claim ⁵⁶39 wherein the communication signal includes first and second time slots separated by a guard period, and the insertion phase variation compensation module adjusts the phase of the communication signal based on the provided estimate during the guard period after data in the first time slot is received by the amplifier and is processed.

74 88. (new): The method of claim ⁷³49 wherein the communication signal includes first and second time slots separated by a guard period, and at least one of steps (a) - (d) are implemented during the guard period after data in the first time slot is received by the amplifier and is processed.

75 89. (new): The method of claim ⁷³49 wherein the communication signal includes first and second time slots separated by a guard period such that data in the first time slot is received by the amplifier when the amplifier is disabled and data in the second time slot is received by the amplifier when ^{the amplifier} it is enabled.

77 90. (new): The method of claim ⁷⁶55 wherein the communication signal includes first and second time slots separated by a guard period, and at least one of steps (a) - (d) are implemented during the guard period after data in the first time slot is received by the amplifier and is processed.

Applicant: Demir et al.
Application No.: 10/736,381

78 91. (new): The method of claim ⁷⁶55 wherein the communication signal includes first and second time slots separated by a guard period such that data in the first time slot is received by the amplifier when ^{the amplifier}it is enabled and data in the second time slot is received by the amplifier when the amplifier is disabled.